



## Technical Data

07.2021

	<b>F8 CLASSIC</b> stainless steel	<b>F8 CLASSIC</b> hot-dip galvanised	<b>F8 LIVE</b> stainless steel	<b>F8 LIVE</b> hot-dip galvanised	<b>F8 LIVE EXTRA</b> hot-dip galvanised	<b>F8 LIVE INTENSE</b> hot-dip galvanised
Solar module	monocrystalline	monocrystalline	monocrystalline	monocrystalline	monocrystalline	monocrystalline
Output	60/58Wp	60Wp	60Wp	60Wp	120Wp	120Wp
Inclination	45°	adjustable 30° / 45° / 60° / 75° / 90°	45°	adjustable 30° / 45° / 60° / 75° / 90°	adjustable 30° / 45° / 60° / 75° / 90°	adjustable 30° / 45° / 60° / 75° / 90°
Options	with frame/frameless	with frame	with frame/frameless	with frame	with frame	with frame
Height of light	4,1m	3,4m / 4,1m	4,1m	3,4m / 4,1m	3,4m / 4,1m / 5,1m	4,1m / 5,1m
LED	12 (>100.000h)	12 (>100.000h)	12 (>100.000h)	12 (>100.000h)	12 (>100.000h)	2x12 (>100.000h)
Lumen	680 lm	680 lm	680 lm	680 lm	820 lm	1.700-2.150 lm
Colour temp.	Standard: 4.000k Alternative: 2.200K/3.000K/6.500K	Standard: 4.000k Alternative: 2.200K/3.000K/6.500K	Standard: 4.000k Alternative: 2.200K/3.000K/6.500K	Standard: 4.000k Alternative: 2.200K/3.000K/6.500K	Standard: 4.000k Alternative: 2.200K/3.000K/6.500K	Standard: 4.000k Alternative: 2.200K/3.000K/6.500K
online-condition monitoring	no	no	yes	yes	yes	yes
Motion sensor	no	no	yes	yes	yes	yes
Battery (inside pole)	NiMh	NiMh	NiMh	NiMh	NiMh	NiMh
Length of pole	4,8m	4,0m / 4,8m	4,8m	4,0m / 4,8m	4,0m / 4,8m / 5,8m	4,8m / 5,8m